

- 15 SEER HIGH EFFICIENCY
- ECO-FRIENDLY R410A
- TURBO COOLING FUNCTION
- SLEEP MODE
- SELF CLEANING EVAPORATOR
- STYLISH DESIGN WITH LED DISPLAY
- ACTIVE CARBON FILTER
- EASY TO INSTALL
- QUIET OPERATION



## Biō INVERTER™ Viü

### 15 SEER INVERTER MINI SPLIT




Innovair's Bio-Inverter Viü delivers a full line of inverter systems ranging from 12,000 BTU to 24,000 BTU! At a 15 SEER rating, this Inverter can save you money on monthly electric bills with a low start up cost.

The Bio-Inverter Viü indoor unit included an elegant mirror panel and LED Display with an easy to use LCD remote control. The unit is also hardly noticeable to one's ear with its quiet sound level. Without notice, the room will be cooled down for ultimate comfort.



Turbo Sleep Mode (7hr off) Auto-Restart Function LED Display Active Carbon Filter Auto Level Swing

#### DC INVERTER 180° SINE WAVE



- Applicable wider range of Frequency & Voltage
- More Efficient & Energy Saving
- Smooth Running low noise and vibration
- More Reliable in operation

#### INVERTER TECHNOLOGY


- Start-up time is reduced by about 30%
- Comfort temperatures are reached quicker
- Small temperature fluctuations
- Energy savings of 30-40% over conventional condensers
- Minimizes compressor cycling, reducing costly voltage peaks
- Quieter operation

MODEL		BIN414C1V32-V	BIN312C2V32-V	BIN414C2V32-V	BIN520C2V32-V	BIN625C2V32-V	
SYSTEM	CERTIFICADO	AHRI	-	-	6087019	6087020	6087021
	CAPACITY	Range (BTU/H)	4,000 ~ 14,000	3,000 ~ 12,000	4,000 ~ 14,000	5,000 ~ 20,000	6,000 ~ 25,000
	EFFICIENCY	SEER	15	15	15	15	15
	POWER SUPPLY	Volt-Phase-Hertz	115V-1Ph-60Hz	220/230V-1Ph-60Hz			
		Rated Current (A)	9.5 ~ 12.2	1.2 ~ 5.5	1.4 ~ 6.0	1.8 ~ 10.2	3.6 ~ 12.5
		Range (Volts)	103 ~ 127v	190 ~ 254V			
		Max Current (A)	20.0	10.0	10.0	14.0	16.0
	OPER. AMBIENT TEMP.	(°F)	64° ~ 122°				
	APPLICATION AREA	(Ft²)	150 - 320	100 - 250	150 - 320	230 - 470	320 - 625
	MOISTURE REMOVAL	Liter/Hr	1.2	1	1.2	1.8	2.4
	REFRIGERANT	R410A (g)	900	550	650	850	1180
	REFRIGERANT CONNECTIONS	Flare/Sweat	FLARE				
		Liquid (in)	1/4"	1/4"	1/4"	1/4"	3/8"
		Suction (in)	1/2"	3/8"	1/2"	1/2"	5/8"
Maximum Length (Ft)		66	66	66	82	82	
Maximum Height (Ft)		26	26	26	33	33	
INDOOR UNIT	AIR FLOW	CFM	235 ~ 341	206 ~ 283	265 ~ 371	330 ~ 430	530 ~ 647
	MOTOR	RPM (High/Med/Low)	860/760/660	890/830/770	940/888/835	860/760/660	930/880/830
	INDOOR FAN	Type	THERMO-FIBER PLASTIC SCROLL FAN				
	SOUND LEVEL	dB(A)	39 ~ 29	39 ~ 28	39 ~ 31	42 ~ 31	47 ~ 39
	CONTROL	Remote Control	LCD DIGITAL DISPLAY				
		Auto Restart	YES				
		Protection	TIME DELAY-SOFT START				
	DIMENSIONS	Unit W x H x D (in)	30¼ x 10 x 7½	26¾ x 10 x 7	30¼ x 10 x 7½	35½ x 10¾ x 7¾	40½ x 12½ x 8½
		Packaging W x H x D (in)	32¾ x 13 x 10½	29½ x 13 x 10	32¾ x 13 x 10½	38¼ x 13½ x 10½	44 x 15½ x 11¼
	WEIGHT	Net/Gross (Lbs.)	17 / 21	16 / 18	17 / 21	20 / 26	27 / 33
OUTDOOR UNIT	AIR FLOW	CFM	825	970	1,060	1,290	1,590
	MOTOR	RPM(High/Low)	860/660	890/770	940/835	860/680	930/830
	COMPRESSOR	RLA	4.95	4.95	5.30	3.95	9.70
		R410a (g)	900g	550g	650g	850g	1180g
	SOUND LEVEL	dB(A)	55	53	55	59	59
	DIMENSIONS	Unit W x H x D (in)	26 x 21½ x 10½	27½ x 21¼ x 9½	30¾ x 21¼ x 9¾	30 x 23¼ x 11¼	33¼ x 27½ x 13¼
		Packaging W x H x D (in)	31 x 24½ x 14	32¼ x 22¾ x 12¾	35¾ x 23 x 13¼	35 x 25½ x 14	38 x 29¾ x 15½
	WEIGHT	Net/Gross (Lbs.)	65.0/72.6	55.1/59.5	61.7/66.2	76.0/81.6	98.1/105.8


\* Specifications are subject to changes without notice.

\*\* Model numbers, pictures, and specifications of all products are subject to change without further notice.


### PERFECT FOR



BED ROOM



LIVING ROOM



GARAGE



### ACCESSORIES INCLUDED

- 3 Meter installation kit
- Inter-connecting cable kit
- Installation Manual
- Plastic cover for valves
- LCD Wireless remote control

Distributed by:



© 2015 Innovair Corporation. All Rights Reserved.

Connect with us



www.innovair.com

INNEINVIUE150201