







- AHRI CERTIFIED
- R410a ECO-FRIENDLY
- 20 SEER EFFICIENCY
- TURBO COOLING FUNCTION
- SLEEP MODE
- STYLISH DESIGN WITH LED DISPLAY
- SELF CLEANING EVAPORATOR
- EASY TO INSTALL
- QUIET OPERATION



## NEXXOS INVERTER™

### 20 SEER INVERTER MINI SPLIT



-  Turbo
-  LED display
-  Sleep Mode (7hr off)
-  Leak Detection
-  Auto-Restart Function
-  Auto Level Swing

#### DC INVERTER 180° SINE WAVE



-  Applicable wider range of Frequency & Voltage
-  More Efficient & Energy Saving
-  Smooth Running low noise and vibration
-  More Reliable in operation

#### INVERTER TECHNOLOGY

- Start-up time is reduced by about 30%
- Comfort temperatures are reached quicker
- Small temperature fluctuations
- Energy savings of 30-40% over conventional condensers
- Minimizes compressor cycling, reducing costly voltage peaks
- Quieter operation

SYSTEM	MODEL	NIN415C2V32	NIN520C2V32	NIN725C2V32	
	CERTIFICATE	AHRI	YES	YES	YES
	CAPACITY	Range (BTU/H)	4,000 ~ 15,000	5,000 ~ 20,000	7,000 ~ 25,000
	EFFICIENCY	SEER	20	20	20
	ELECTRICAL	Volt-Phase-Hertz	220/230V-1Ph-60Hz		
		Rated Current (A)	4.0	6.3	7.7
		Range (Volts)	190 ~ 254V		
		Min Circuit (A)	15.0	14.0	15.0
	OPER. AMBIENT TEMP.	(°F)	64° ~ 122°		
	APPLICATION AREA	(Ft²)	180 ~ 420	480 ~ 635	625 ~ 850
MOISTURE REMOVAL	Liter/Hr	1.2	1.8	2.4	
REFRIGERANT CONNECTIONS	Flare/Sweat	FLARE			
	Liquid (in)	1/4"	1/4"	3/8"	
	Suction (in)	1/2"	1/2"	5/8"	
	Maximum Length (Ft)	82	98	98	
	Maximum Height (Ft)	33	66	66	

INDOOR UNIT	AIR FLOW	CFM	320	700	650
	MOTOR	RPM (High/Med/Low)	1250 / 1000 / 850	1200 / 1100 / 900	1200 / 1100 / 900
	INDOOR FAN	Type	THERMO-FIBER PLASTIC SCROLL FAN		
	SOUND LEVEL	dB(A)	44 ~ 28	50 ~ 31	51 ~ 39
	CONTROL	Remote Control	LCD DIGITAL DISPLAY		
		Auto Restart	YES		
		Protection	TIME DELAY SOFT START		
	DIMENSIONS	Unit W x H x D (in)	31 1/2 x 10 3/4 x 7 1/2	41 x 12 1/2 x 9 1/4	41 x 12 1/2 x 9 1/4
		Packaging W x H x D (in)	34 x 13 3/4 x 10 1/2	44 1/2 x 12 1/2 x 15 1/2	44 1/2 x 12 1/2 x 15 1/2
	WEIGHT	Net/Gross (Lbs.)	20 / 26	26 / 34	27 / 35

OUTDOOR UNIT	AIR FLOW	CFM	1150	1470	2350
	MOTOR	RPM(High/Low)	800/700/600	800/750/700	850/750/700
	COMPRESSOR	RLA	5.3	9.7	8.9
		R410a (g)	870g	1150g	2350g
	SOUND LEVEL	dB(A)	55	60	60
		Unit W x H x D (in)	32 x 22 x 12 1/4	33 1/4 x 27 1/2 x 12 1/2	37 1/4 x 32 x 15 1/2
		Packaging W x H x D (in)	36 3/4 x 24 1/4 x 15 3/4	38 x 29 3/4 x 15 1/2	43 x 33 3/4 x 18 3/4
	WEIGHT	Net/Gross (Lbs.)	68 / 73	90 / 98	136 / 147

\* Specifications are subject to changes without notice.

\*\* Model numbers, pictures, and specifications of all products are subject to change without further notice.

PERFECT FOR



BEDROOM



LIVING ROOM



GARAGE



ACCESSORIES INCLUDED

- 3 Meter installation kit
- Inter-connecting cable kit
- Installation Manual
- Plastic cover for valves
- LCD Wireless remote control

Distributed by:



© 2015 Innovair Corporation. All Rights Reserved.

Connect with us



www.innovair.com

INNEINVIUE151101